



Coppia di ricetrasmittitori passivi video HDCVI/TVI/AHD (4Mp, 6Mp, 8Mp)

Coppia di ricetrasmittitori passivi video HDCVI/TVI/AHD monocanale su singola coppia UTP, portata 400mt a 720p o 250 a 1.080p, 200mt a 4Mp/6Mp/4K con attacco BNC maschio e cavo da 8cm + 1 RJ45 e morsetti



CARATTERISTICHE TECNICHE

Technical Specification		ACE504K		
Transmission Signal	1-CH			
Network cable Type	UTP CAT5E/6 (material: CU)			
Transmission Properties	HDCVI	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/6M/4K : max.200m (656.17ft)
	TVI	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M : max.200m (656.17ft)
	AHD	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M : max.200m (656.17ft)
Video Transmission Properties				
Coaxial Video Connector	BNC-M			
Connection Way	RJ45			
Compatible Format	HDCVI/TVI/AHD/CVBS			
Resolution	720P/1080P/4MP/5MP/4K			
Protection				
ESD	1a contact discharge electricity level 3			
	1b air discharge electricity level 3 Per: IEC61000-4-2			
UTP Cable Connector	2KV(different-mode), 4KV(common-mode) Per: IEC61000-4-5			
Impedance				
BNC Male Impedance	75 ohms			
UTP Cable Impedance	100 ohms			
Physical Properties				
Weight	40g (0.09lb) (1 pair)			
Dimension(LxWxH)	173.8mmx19.5mmx21mm (6.84"x0.77"x0.83")			
Shell	ABS			
Color	Black			
Environmental				
Operating Temperature	-30°C~+70°C(-22°F~+158°F)			
Operating Humidity	<95% RH			
Storage Temperature	-40°C~+80°C(-40°F~+176°F)			

