




Camera IP ePoE Dome 4Mp Ottica Motorizzata 2,7-13,5mm

Camera IP Dome ePoE IP67 risoluzione 4Mp con 25Fps, con analisi video, sensore CMOS progressivo 1/3", H265+/H264, ICR meccanico, ottica motorizzata 2.7~13.5mm, luminosità 0,03Lux/F1.4 (0 Lux con IR on), led IR portata fino a 50mt, 1 slot per MicroSD-Card (max 128Gb), porta LAN 10/100, microfono, privacy mask 4 aree, 3D, WDR, face detection, alimentazione 12Vdc o ePoE o PoE <8,5W, compatibile ONVIF



ACCESSORI (OPTIONAL)




ACM207



ACM253



ACM262



ACM202

CARATTERISTICHE TECNICHE

Camera	NDV404ME				
Image Sensor	1/3" 4Megapixel progressive scan CMOS				
Effective Pixels	2688(H)x1520(V)				
RAM/ROM	512MB/32MB				
Scanning System	Progressive				
Electronic Shutter Speed	Auto/Manual, 1/3~1/100000s				
Minimum Illumination	0.03Lux/F1.6 (Color, 1/3s, 30IRE) 0.3Lux/F1.6 (Color, 1/30s, 30IRE) 0Lux/F1.6(IR on)				
S/N Ratio	More than 50dB				
IR Distance	Distance up to 50m (164ft)				
IR On/Off Control	Auto/ Manual				
IR LEDs	2				
Lens					
Lens Type	Motorized/ Auto Iris(DC)				
Mount Type	Board-in				
Focal Length	2.7mm~13.5mm				
Max. Aperture	F1.6				
Angle of View	H: 106°~31°, V: 58°~17°				
Optical Zoom	5x				
Focus Control	Motorized				
Close Focus Distance	0.3m				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	W	64(210ft)	26m(85ft)	13m(42ft)	6.5m(21ft)
	T	208m(682ft)	83m(272ft)	41m(136ft)	20m(68ft)
Pan/Tilt/Rotation					
Pan/Tilt/Rotation Range	Pan:0°~360°; Tilt:0°~78°; Rotation:0°~360°				
Intelligence					
IVS	Tripwire, Intrusion, Object Abandoned/Missing				
Advanced Intelligent Functions	Face Detection				
Video					
Compression	H.265+/H.265/H.264+/H.264				
Streaming Capability	3 Streams				
Resolution	4M(2688x1520)/3M(2304x1296)/1080P(1920x1080)/1.3M(1280x960)/720P(1280x720)/D1(704x576)/704x480/VGA(640x480)/CIF(352x288/352x240)				
Frame Rate	Main Stream: 4M(1~25/30fps) Sub Stream: D1(1~25/30fps) Third Stream: 720P(1~25/30fps)				
Bit Rate Control	CBR/VBR				
Bit Rate	H.264: 24~1024Kbps H.265: 14~9984Kbps				
Day/Night	Auto(ICR) / Color / B/W				
BLC Mode	BLC / HLC / WDR(120dB)				
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual				
Gain Control	Auto/Manual				
Noise Reduction	3D DNR				
Motion Detection	Off / On (4 Zone, Rectangle)				
Region of Interest	Off / On (4 Zone)				
Electronic Image Stabilization (EIS)	N/A				
Smart IR	Support				
Defog	N/A				
Digital Zoom	16x				
Flip	0°/90°/180°/270°				
Mirror	Off / On				
Privacy Masking	Off / On (4 Area, Rectangle)				
Audio					
Compression	G.711a/ G.711mu/ AAC/ G.726				
Network					
Ethernet	RJ-45 (10/100Base-T)				
Protocol	HTTP, HTTPS, TCP, ARP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, QoS, UPnP/NTP, Bonjour, 802.1x, Multicast, ICMP, IGMP, SNMP				
Interoperability	ONVIF, PSIA, CGI				
Streaming Method	Unicast / Multicast				
Max. User Access	10 Users /20 Users				
Edge Storage	NAS Local PC for instant recording Mirco SD card 128GB				
Web Viewer	IE, Chrome, Firefox, Safari				
Management Software	Smart PSS, DSS, Easy4ip				
Smart Phone	IOS, Android				
Interface					
Video Interface	N/A				
Audio Interface	Built-in Mic				
RS485	N/A				
Alarm	N/A				
Electrical					
Power Supply	DC12V, PoE(802.3af)(Class 0)				
Power Consumption	<8.5W				
Environmental					
Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH				
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH				
Ingress Protection	IP67				
Vandal Resistance	N/A				
Construction					
Casing	Metal				
Dimensions	Ø122mm×104mm(4.8"×4.09")				
Net Weight	0.6Kg (1.32lb)				
Gross Weight	0.76Kg (1.67lb)				