ACE022

PIXVIDEO

Coppia Wireless bridge 2,4GHz e 300Mbps

distanza di trasmissione fino a 500 metri. Il prodotto è indicato per tutte le esigenze di installazione di ponti radio con tecnologie punto-punto e punto-multipunto.
Le antenne sono predisposte per l'impostazione facilitata in modalità Master/Slave a realizzare un collegamento di tipo "Bridge" (punto-punto) sul canale radio desiderato e protetto da criptazione WPA.

PIXVIDEO

CARATTERISTICHE TECNICHE

Model	ACE022
Main Chip	MTK7628KN 300Mbps
Wireless Technology	2.4G:300Mbps 802.11b/g/n MIMO
Memory	DDR2 8MB
Flash	4MB
Interface	2*10/100 Mbps auto-sensing RJ45 ports
Button	1*Digital Switch/Reset. Value 1 added by short pressing, reset by pressing in 5s.
LED	LAN1/PoE, LAN2, PWR
Power	Passive PoE: 24V 0.5A DC 12V 1A, power consumption < 10W
Antenna	Built-in 12dBi directional antenna with dual polarization
	Horizontal angle: 45 degree, vertical angle: 45 degree.
Operating Environment	Temperature: -30℃ ~ +55℃ (Operation), -40℃ ~ +70℃ (Storage) Humidity (Non-condensing): 10% ~ 90% (Operation),
	5% ~ 95%(Storage)
Dimension	200mm×115mm×60mm
Weight	400g
Modulation	OFDM = BPSK,QPSK,16-QAM,64-QAM;DSSS = DBPSK,DQPSK,CC
Power Output	11a @54M:25±2DB, @6M:27±2DB 11n @MCS7:23±2DB, @MCS0:25±2DB
Frequency Range	ISM: 2.300GHz ~ 2.4835GHz
Operating Channel	2.4G: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 32, 33, 37, 38, 42, 43
Receiver Sensitivity	802.11n: -70dbm@MCS7, -88dbm@MCS0 802.11g: -72dbm@54Mbps, -88dbm@6Mbps 802.11b: -85dbm@11Mbps, -94dbm@1Mbps
Operation Mode	Master AP, Slave AP (Through dial switch)
Networking Mode	Point to Point, Point to multipoint (Within 8 points)
Management	WEB
	Default IP: 169.254.254.254
	Username/Password: utepo/utepo
Network	Bridge: Static IP/ Dynamic IP Gateway: Static IP/ Dynamic IP/ PPPoE
Wireless Management	Bridge configuration, advanced configuration, WIFI confirguration
System	Time/ Date Setting, Username Managerment, Backup/ Restore, Reboot/ Time to Reboot
Update	Local update based on WEB/ Online update

Le immagini e le caratteristiche tecniche possono subire variazioni senza preavviso da parte del produttore