



Switch di rete con 24 porte

Switch di rete con 24 porte PoE 10/100/1000Mbps + 2 porte SFP , alimentazione per porta 30W max, Budget totale 300W. 24 porte PoE autosensing. Le prime 8 porte PoE supportano l'alimentazione fino a 250mt con cavo categoria 6 o superiore. Predisposto per installazione in armadi rack 19". Alimentazione a 220Vac. (440.0x290.0x44.0mm)

PIXVIDEO

CARATTERISTICHE TECNICHE

Standard	IEEE 802.3i IEEE 802.3u IEEE 802.3x IEEE 802.3ab IEEE 802.3af IEEE 802.3at
Port	24 10/100/1000Mbps RJ45 port 2 gigabit SFP port
PoE	24 10/100/1000Mbps RJ45 PoE port Total power budget: 300W Single port max. 30W
Indicator	26 Link/Act indicator light 24 POE indicator light 1 Power indicator light
Performance	Forwarding mode: storage forwarding Bandwidth: 52Gbps Packet forwarding rate: 38.688Mpps Support 8K MAC address list depth
Input power	100-240V/50-60Hz
Dimensions(Lx WxH)	440mmx290mmx44mm

Features

- **AI Extend:** 1-8 port supports 250M meters long distance power supply (recommended cat 5 or above)
- **AI VLAN:** Isolating ports 1-24 from each other, restrain network storms effectively and improve network performance
- **AI QoS:** Customize application prioritization and increase network sensitivity. For example, video priority, monitoring transmission more smoothly
- **AI POE:** Detect PD device and reboot it automatically when it is crash
- Supports IEEE802.3af/at standard, automatically detects and identifies devices that comply with the IEEE 802.3af/at standard and supply power to it
- Support Auto MDI/MDIX;
- Adopt store-and-forward exchange method
- Intelligent power supply, the lowest power consumption, ensure PD power needs
- With power circuit protection, protect the safety of PD
- No configuration characteristics of the power supply is automatically supplied to the adaptive equipment;
- Support port without link power saving function
- All ports have wire-speed forwarding capability
- Plug and play ,easy to use